



# 不锈钢顶式过滤砂缸

## STAINLESS STEEL TOP MOUNT SAND FILTERS

### AQS



#### Maximum working pressure:

4kg/cm<sup>2</sup>(56psi)

#### Maximum temperature:

50°C

Filter material: AISI304

- Stainless steel tank.
- Ergonomically designed six position multiport valve.
- Chemical resistance.
- Pressure gauge for inspection of operating pressure.
- Virtually maintenance free, simply backwash filter when required.
- Beautiful, resistant pressure, no leakage, long service life, preserve value.



最大工作压力:

4kg/cm<sup>2</sup>(56psi)

最高承受温度: 50°C

过滤器材质: AISI304

- 不锈钢缸体;
- 人体工学设计的六向阀门;
- 防化学腐蚀;
- 有监察运作压力的压力表;
- 具有反冲洗功能, 需要时只需简单操作, 从而免去额外的维护费用;
- 美观、耐压、不渗漏、使用寿命长、保值。

### Specification and size:

### 技术参数及产品尺寸

Model 型号	Tank Dia 缸直径 (mm)	Connection Size 接口尺寸	Filter Area 过滤面积 (m <sup>2</sup> )	Flow 流量 (m <sup>3</sup> /h)	Silica Sand 石英砂 (kg)	Height 高 (mm)
AQS400	400	DN40	0.13	6.3	28	740
AQS500	500	DN40	0.22	11.5	80	840
AQS600	600	DN40	0.33	16.5	160	960
AQS700	700	DN40	0.38	19.2	220	1025
AQS800	800	DN50	0.50	25.2	370	1200
AQS900	900	DN50	0.64	32.0	447	1180
AQS1000	1000	DN50	0.79	38.0	650	1220
AQS1200	1200	DN50	1.13	42.0	850	1410