



顶式过滤砂缸

TOP MOUNT SAND FILTERS

**Maximum working pressure:**2.5kg/cm²(35psi)**Maximum temperature:** 45°C**Working pressure of 4kg/cm² available by special order.**

- Tank body has twin heavy duty anti-UV polyurethane protective layer.
- Ergonomically designed six position multiport valve.
- Chemical resistance.
- Pressure gauge for inspection of operating pressure.
- Virtually maintenance free, simply backwash filter when required.
- Sand drain plug for easier sand removal-replacement.

**立体标牌**

Three-dimensional nameplate

最大工作压力:2.5kg/cm²(35psi)**最高承受温度:** 45°C**工作压力为4kg/cm²可按需定制。**

- 缸身有防紫外线的聚氨酯保护层;
- 人体工学设计的六向阀门;
- 防化学腐蚀;
- 有监察运作压力的压力表;
- 具有反冲洗功能需要时只需简单操作,从而免去额外的维护费用;
- 大口径底排砂便于清理或更换缸内的砂。

Specification and size:**技术参数及产品尺寸**

Model 型号	Tank Dia 缸直径 (mm)	Connection Size 接口尺寸	Filter Area 过滤面积 (m ²)	Flow 流量 (m ³ /h)	Silica Sand 石英砂 (kg)	Height 高 (mm)	Weight 重量 (kg)	Matching multi- function valve 匹配多功能阀
Q400	400	DN40	0.13	6.3	30	750	10.3	1.5" 夹箍/螺丝 Clamp/Screw
Q450	450	DN40	0.16	8.0	45	810	12.2	1.5" 夹箍/螺丝 Clamp/Screw
Q500	500	DN40	0.22	11.5	80	870	13.7	1.5" 夹箍/螺丝 Clamp/Screw
Q650	630	DN40	0.33	16.5	130	960	18.4	1.5" 夹箍/螺丝 Clamp/Screw
Q700	700	DN40	0.38	19.2	190	1025	22.6	1.5" 夹箍/螺丝 Clamp/Screw
Q800	800	DN50	0.50	25.2	260	1130	27.7	2" 螺丝 Screw
Q900	900	DN50	0.64	30.0	400	1270	34.5	2" 螺丝 Screw
Q1000	1000	DN50	0.79	34.0	600	1340	46.0	2" 螺丝 Screw
Q1100	1100	DN50	0.95	38.0	800	1460	50.5	2" 螺丝 Screw
Q1200	1200	DN50	1.13	42.0	900	1540	62.0	2" 螺丝 Screw
Q1400	1400	DN50	1.54	48.0	1600	1750	73.0	2" 螺丝 Screw