

AQUA<sup>®</sup>  
爱克

The quality come from life  
品质源自于生活



## 双功能水质监控仪

ORP AND PH CONTROL SYSTEM

双行16字液晶显示

16 Words Double Line LCD

\*意大利原装进口

\*Original imported from Italy



The quality come from life  
品质源自于生活

## 双功能水质监控仪 ORP AND PH CONTROL SYSTEM

AUT-042



Original imported from Italy, Using high quality electronic components and excellent housing material, is a pool water quality intelligent monitoring system, designed to control residential and commercial swimming pool and SPA pool water chlorine content and PH value.

意大利原装进口，采用高品质电子元器件和优良的外壳材质制造而成，是一款泳池水质智能监控系统，设计用于控制家用及商用泳池及SPA池水的氯含量及PH值。

### Feature:

PH measurement-- range: 0~14; Resolution:  $\pm 0.01$   
ORP measurement -- range:  $\pm 1500\text{mV}$ ;  
Resolution: 1mV; Accuracy:  $\pm 1\text{mV}$   
Power input --100 ~ 240V, 50 ~ 60Hz  
Signal Input -- external trigger (flow meter) input  
(15 ~ 30Vac / Vdc)  
Output --0 / 4 ~ 20mA, 4 dosing pump relay output  
(10A, 250V)  
Power --15W  
Dimensions --300 (H)  $\times$  290 (W)  $\times$  143 (D)  
Installation -- wall-mounting  
Working environment -- Temperature: 0 ~ 40 °C;  
Relative Humidity: 0 ~ 95% (non-condensing)  
Weight --2.45kg  
Housing material --ABS  
Protection degree --IP65

### Accessories:

### 特点:

PH测量--范围: 0~14; 分辨率:  $\pm 0.01$   
ORP测量--范围  $\pm 1500\text{mV}$ ; 分辨率: 1mV; 精度:  $\pm 1\text{mV}$   
电源输入--100~240V, 50~60Hz  
信号输入--外部触发(流量计)输入(15~30Vac/Vdc)  
输出--0/4~20mA, 4个加药泵继电器输出(10A, 250V)  
功率--15W  
外形尺寸--300(高) $\times$ 290(宽) $\times$ 143(深)  
安装方式--挂壁式  
工作环境--温度: 0~40°C; 相对湿度:0~95%(无冷凝)  
重量--2.45kg  
外壳材质--ABS  
防护等级--IP65

### 配件:

